

# Band Slicer



**LeMatic**

*Cooler to the door*

**Single: BF15/BF15W**  
**Double: BF25/25W**

## FEATURES

- Single-through slicing (BF15 or BF15W models)
- Single or double-through slicing (BF25 or BF25W models)
- Optional floating head pressure design produces a consistent quality slice
- Completely adjustable for slicing height and top conveyor pressure
- Slicer can be power-raised out of position to bypass unsliced product
- Slicer can be mounted on existing LeMatic frame or with a revised design for customer-supplied frame
- Design emphasizes safety and reliability, straight forward operation and complete accessibility for maintenance and sanitation



*Shown with  
optional conveyor*

*Designed to perform. Backed by experience.*

# Band Slicer

**Single: BF15/BF15W**  
**Double: BF25/25W**

## GENERAL SPECIFICATIONS:

- Production Rate: Exceeding 1200 pcs./min. based on 4" round roll
- Electrical: All standard voltages
- Control Voltage: 24VDC, other voltages available
- Air Requirements: Slicer dependent
- Slicer Head Drive: 1½ HP w/brake (each blade drive)

## OPTIONS:

- Slicer head for a 26" [660mm] or 34" [863mm] wide belt conveyor
- UL, CUL/CSA, CE compliance
- Wash-down construction
- Floating Top Conveyor (FTC) for special slicing requirements

Model	Belt Width "A" In. [mm]	Frame Width "B" In. [mm]	Machine Width "C" In. [mm]
BF-15	26 [660]	34½ [876]	62 [1575]
BF-15W	34 [864]	42.5 [1079]	70 [1778]
BF-25 (Shown)	26 [660]	34.5 [876]	81 [2057]
BF-25W	34 [864]	42.5 [1079]	88.5 [2248]

