



LeMatic

Cooler to the door

Band Slicer

Single: BF-15/BF-15W

Double: BF-25/BF-25W

FEATURES

- Single-through slicing (BF-15 or BF-15W models)
- Single or double-through slicing (BF-25 or BF-25W models)
- Optional floating head pressure design produces a consistent quality slice
- Completely adjustable for slicing height and top conveyor pressure
- Slicer can be power-raised out of position to bypass unsliced product
- Slicer can be mounted on existing LeMatic frame or with a revised design for customer-supplied frame
- Design emphasizes safety and reliability, straight forward operation and complete accessibility for maintenance and sanitation



Output view of BF-25W



Infeed view of BF-25W

Band Slicer

Single: BF-15/BF-15W
Double: BF-25/BF-25W

GENERAL SPECIFICATIONS:

- Production Rate: Exceeding 1200 pcs./min. based on 4" round roll
- Electrical: All standard voltages
- Control Voltage: 24VDC, other voltages available
- Air Requirements: Slicer dependent
- Slicer Head Drive: 1½ HP w/brake (each blade drive)

OPTIONS:

- Slicer head for a 26" [660mm] or 34" [863mm] wide belt conveyor
- UL, CUL/CSA, CE compliance
- Wash-down construction
- Floating Top Conveyor (FTC) for special slicing requirements

Model	Belt Width "A"	Frame Width "B"	Machine Width "C"
	In. [mm]	In. [mm]	In. [mm]
BF-15	26 [660]	34.5 [876]	66.5 [1689]
BF-15W	34 [864]	42.5 [1079]	74 [1880]
BF-25 (Shown)	26 [660]	34.5 [876]	85.5 [2172]
BF-25W	34 [864]	42.5 [1079]	93 [2362]

